

Architectural 19W PAR38 1250LM Dimmable

CIVILIGHT®




Features

- CRI 95, R9=80(2700K), R9=84(3000K)
- Glare-free
- Smart heat sinking design
- Smooth dimming
- 100W halogen equivalent
- 81% energy saving

Applications

- Track lighting
- Recessed downlight
- Ambient and accent lighting

Part No.	DPAR38	DPAR38	DPAR38	DPAR38	DPAR38	DPAR38
	KP01Q19	KP01Q19	WP01Q19	WP01Q19	NP01Q19	NP01Q19
	- 44022	- 44023	- 44028	- 44029	- 44034	- 44035
Wattage (W)	19	19	19	19	19	19
HALOGEN Equivalent (W)	100	100	100	100	100	100
Dimmable	Yes	Yes	Yes	Yes	Yes	Yes
Socket	E26	E26	E26	E26	E26	E26
Lumens (lm)	1250	1150	1250	1250	1300	1300
Luminous Intensity (cd)	4250	2100	4450	2250	4800	2300
PF	0.8	0.8	0.8	0.8	0.8	0.8
CCT (K)	2700	2700	3000	3000	4000	4000
CRI (Ra)	95	95	95	95	95	95
Voltage (V)	120	120	120	120	120	120
Current (A)	0.2	0.2	0.2	0.2	0.2	0.2
Frequency (Hz)	60	60	60	60	60	60
Beam Angle (deg)	25°	40°	25°	40°	25°	40°
Lifespan (hrs)	40000	40000	40000	40000	40000	40000
Working Temperature (°C)	-20 ~ 40	-20 ~ 40	-20 ~ 40	-20 ~ 40	-20 ~ 40	-20 ~ 40
Storage Temperature (°C)	-20 ~ 85	-20 ~ 85	-20 ~ 85	-20 ~ 85	-20 ~ 85	-20 ~ 85
Weight (ounces)	15.52	15.52	15.52	15.52	15.52	15.52
Energy Star	Yes		Yes	Yes		



At \$0.11 per kWh, this 19W LED PAR38 bulb estimates energy cost \$2.29 per year, using \$83.6 of electricity over its 40000 hour lifetime. This is a \$356.4 savings when compared to the \$440 required to run a 100W halogen PAR38 over the same period. Actual savings will vary depending on cost per kWh. 36.5 years means rated average life based on engineering testing and probability analysis where the lamp is used 3 hours per day, 7 days a week.

* Note: Data is subject to change without prior notice. Please visit www.civilight-na.com for further information.

Cautions

- Power off before replacing
- Don't touch lamp when lit



CIVILIGHT NORTH AMERICA CORP

Address: 522 Buxton Grant Drive, Cary, NC 27519
 TEL: 919-234-0853 / WEB: www.civilight-na.com