

# Architectural 6.5W LED Omni A19 450LM Dimmable CIVILIGHT®




## Features

- CRI 97, R9=80
- Omni-directional
- 40W incandescent equivalent
- 82% energy saving
- Smooth dimming
- UL and RoHS compliant

## Applications

- Home, apartment and other residential buildings
- Hotels, restaurants, bars

Part No.	DA19 K2F40Q7-16430	DA19 W2F40Q7-16431	DA19 DF40Q7-16432
Wattage (W)	6.5	6.5	6.5
Incandescent Equivalent (W)	40W	40W	40W
Dimmable	Yes	Yes	Yes
Socket	E26	E26	E26
Lumens (lm)	450	450	450
Luminous Efficiency (lm/W)	75	75	75
PF	>0.7	>0.7	>0.7
CCT (K)	2700	3000	5000
CRI (Ra)	97	93+	90
Voltage (V)	120	120	120
Current (A)	0.080	0.080	0.080
Frequency (Hz)	60	60	60
Beam Angle (deg)	Omni	Omni	Omni
Lifespan (hrs)	25000	25000	25000
Working Temperature (°C)	-20 ~ 40	-20 ~ 40	-20 ~ 40
Storage Temperature (°C)	-20 ~ 85	-20 ~ 85	-20 ~ 85
Weight (ounces)	4.06	4.06	4.06



At \$0.11 per kWh, this 6.5W LED bulb estimates energy cost \$0.78 per year, using \$17.88 of electricity over its 25000 hour lifetime. This is a \$92.12 savings when compared to the \$110 required to run a 40W incandescent over the same period. Actual savings will vary depending on cost per kWh. 22.8 years means rated average life based on engineering testing and probability analysis where the lamp is used 3 hours per day, 7 days a week.

\* Note: Data is subject to change without prior notice. Please visit [www.civilight-na.com](http://www.civilight-na.com) for further information.

## Cautions

- Power off before replacing
- Don't touch lamp when lit



**CIVILIGHT NORTH AMERICA CORP**

Address: 522 Buxton Grant Drive, Cary, NC 27519  
TEL: 919-234-0853 / WEB: [www.civilight-na.com](http://www.civilight-na.com)